Cree LED wall lamp Amarante | warm white | 3 watt | up or down

Product Images

×



The Cree LED wall light Amarante is suitable for mounting against a wall, wall, or fence. The wall light is equipped with 1 spot with a warm white light of 3 watts. You can choose whether the spot shines up or down. The working voltage of this lamp is 230 volts.

Description

The Amarante wall light is a real atmosphere creator. The wall light is equipped with 1 spot of 3 watts, which with its warm white light (2700k) ensures that your garden is illuminated attractively. By tilting the wall lamp you can determine whether the wall lamp shines up or down. The Amarante wall light is powder coated and therefore fully weatherproof. This is confirmed once again by the IP-65 value of this wall light. The wall lamp comes with a 40 cm long 3-core cable. You need to connect this directly to a 230-volt power cable.

The 3-wire cable of the wall light can be easily connected to a 230-volt power cable with waterproof cable connectors. These waterproof cable connectors are available from our webshop. Would you like to make this wall light smarter by connecting it to a twilight switch and motion detector? That is possible! Both are available on our webshop.

Tip: With waterproof cable connectors you can connect multiple 230-volt garden lights.

This wall light comes with a 5-year guarantee. Do you need advice or have a question about the Amarante wall light? Feel free to contact our LED specialists. For more information about this wall light, you can also view the product specifications.

Additional Information

EAN code	7435124531544
Article number	L2095
Brand	Hamulight
Suitable for	Outside
Consumption	3 watt
Input voltage	230V AC
LED chip	Cree
Dimmable	No
Light color	Warm white (2700K)
Lumen per LED (including lens)	90 lm
Color Rendering Index (CRI)	>92
Light angle	3 Degrees
Cabling per LED	100 cm
Transformer required?	No
Diameter	60 mm
Width	80 mm
Height	130 mm
Material	Aluminium
IP value	IP65
Quality mark	CE, Rohs
Guarantee	5 years
Spot color	Aluminium
Energy label old	A++
Energy label new	G